



8461M

SINGLE-FAMILY KIT WITH QUADRA AND MINI, SIMPLEBUS SYSTEM



2-wire Simplebus door entry monitor kit comprised of: 1 Quadra series wall-mounted external unit art. 4893M, 1 power supply unit art. 1209, 1 Mini series color monitor art. 6701W, 1 distribution terminal art. 1214/2C and 1 line closure terminal art. 1216.

AWARDS





8461M

SINGLE-FAMILY KIT WITH QUADRA AND MINI, SIMPLEBUS SYSTEM



4893M QUADRA ENTRANCE PANEL W/ BUTTONS. 2 WIRES

Quadra series wall-mounted external video entry unit with mechanical buttons. Die-cast aluminium faceplate, wide-angle colour camera and a single LED for nighttime lighting. Indicator LED for call sent, lock-release activated, audio activated and system busy. Adjustment of speaker volume and audio balance. Power supply from bus line. External unit dimensions: 95x195x28 mm.

GENERAL DATA	
Type	Monoblock
Height (mm)	195
Width (mm)	95
Depth (mm)	28
Product weight (g)	300
Product color	Grey RAL 9006, Black RAL9005
Wall-mounted	Yes

COMPATIBLE SYSTEMS	
Simplebus 2 audio/video kit with power supply art. 1209	Yes

AUDIO FEATURES	
Microphone	6mm (Ø), Omnidirectional
Loudspeaker	36mm (Ø), 8 Ohm, 1W

CAMERA FEATURES	
Camera	Colours
Sensor type	1/4" CMOS
Lens optical dimensions (mm)	2.1
Angle of view (H x V - °)	85 x 72
Sensitivity (lux)	0.1 (colour)



8461M

SINGLE-FAMILY KIT WITH QUADRA AND MINI, SIMPLEBUS SYSTEM

Type of power supply	Power supply from video door entry bus
Supply voltage	33VDC
Maximum absorption (W)	8.25

HARDWARE FEATURES

Call type	Push-buttons
Type of buttons	Mechanical
Number of push-buttons (n°)	4
Backlight colour	White
Clamps	LL RTE COM DO SE- SE+C NC NO
Number of inputs (n°)	2
Number of outputs (n°)	2
Type of outputs	Relay (C-NO-NC, 10A@12÷24 VAC/VDC), SE: unlock pulse of 4A, holding current of 200mA for 12VAC / DC locks (maximum impedance 18 Ohm)

SETTINGS

Loudspeaker volume	Yes
Microphone volume	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP54
Vandal Resistant rating (IK code)	IK08
Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	IV
CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

MAIN FUNCTIONS

Door opener	Yes
-------------	-----



8461M

SINGLE-FAMILY KIT WITH QUADRA AND MINI, SIMPLEBUS SYSTEM

Number of auxiliary relays (n°)	1
Input for local door release button	Yes
Door open signaling input	Yes

GENERAL FEATURES

Type of finishing materials	Polycarbonate, Aluminium alloy
Acoustic signalling	Yes
Visual signalling	Yes
Speech synthesis	Yes



8461M

SINGLE-FAMILY KIT WITH QUADRA AND MINI, SIMPLEBUS SYSTEM



6701W SIMPLEBUS2 MINI DOOR ENTRY MONITOR WITH HANDSET

Wall-mounted colour monitor with 4.3" 16:9 screen and handset. Allows brightness and contrast control, plus adjustment of the volume of the ringtone, which can be customised with a choice of different melodies. Equipped as standard with 4 soft touch buttons for door-opening, self activation, switchboard call, silent mode and with door status indicator LEDs. Manages floor door calls as standard. Option of adding 4 additional buttons with accessory art. 6733W. Complete with 2 x 8-position DIP-switches for user code programming and button programming. Includes wall-mounting or residential series box backplate and riser distribution terminal art. 1214/2C. The monitor can only be used in 2-wire Simplebus2 systems. Dimensions: 175x160x22mm.

GENERAL DATA

Height (mm)	160
Width (mm)	175
Depth (mm)	22
Product color	White RAL9003
Type of finishing materials	ABS
Product weight (g)	600
Wall-mounted	Yes
Desk base-mounted	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS

Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes

DISPLAY

Display size (")	4.3
Aspect Ratio	16:9

The technical specifications are subject to change without prior notice.



8461M

SINGLE-FAMILY KIT WITH QUADRA AND MINI, SIMPLEBUS SYSTEM

Resolution (pixels)	480x272
---------------------	---------

AUDIO FEATURES

Microphone	6mm (Ø), Omnidirectional
Loudspeaker	40 (ø) x 5.1 (H)mm, 100 ohm, 0.25W

ELECTRICAL CHARACTERISTICS

Type of power supply	Power supply from video door entry bus
Supply voltage	22 ÷ 34 VDC (Bus)
Maximum absorption (W)	5.4

HARDWARE FEATURES

Type of buttons	Capacitive
Service buttons	Lock-release, Silent (Privacy), Door open
No. of programmable buttons for additional functions	2 (6 with accessory art. 6733W)
Clamps	L L CFP1 CFP2
Removable terminals	Yes

SETTINGS

Ringtone volume	Yes
Screen brightness control	Yes
Screen colour	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP30
Operating temperature (°C)	5 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 75
Environmental class	I
CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)



8461M

SINGLE-FAMILY KIT WITH QUADRA AND MINI, SIMPLEBUS SYSTEM

Door opening on call (Doctor)	Yes
Door opener	Yes
Self Activation	Yes
CPS call	Yes
Intercom calls	Yes
Actuator control	Yes
Multiple address	Yes
Outside door call input	Yes
Sending alarm calls	Yes
Silent mode (Privacy)	Yes
Door open signaling	Yes
Customisable ringtone	Yes



8461M

SINGLE-FAMILY KIT WITH QUADRA AND MINI, SIMPLEBUS SYSTEM



1209 SIMPLEBUS2 VIDEO KIT POWER SUPPLY UNIT

33 VDC power supply unit with overload and short circuit protection devices. It has two separate continuous outputs: one to power the external unit and electric lock, and the other to power the monitor. Input voltage 110-240 VAC. Dimensions: 106x62x89mm (6 DIN modules).

MAIN FEATURES

Supply voltage	110 ÷ 240
Max. current delivered (A)	1.2
Applicable to DIN rail	Yes
Number of DIN modules (n°)	6

GENERAL DATA

Height (mm)	62
Width (mm)	106
Depth (mm)	89
Type of finishing materials	Plastic
Product color	White
Operating temperature (°C)	-5 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 95

COMPATIBILITY

Kit audio/video system	Yes
------------------------	-----

ELECTRICAL SPECIFICATIONS

Maximum power delivered (W)	37
-----------------------------	----



8461M

SINGLE-FAMILY KIT WITH QUADRA AND MINI, SIMPLEBUS SYSTEM



1216 SIMPLEBUS2 LINE TERMINATION TERMINAL

Line termination terminal. To be mounted at the end of the riser, according to the indications given in the technical documentation, to optimise distribution of the signals.

GENERAL FEATURES

Input connector	Terminal block
CE certifications	EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

MAIN FEATURES

Operating temperature (°C)	-5 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 95

COMPATIBILITY

Simplebus 2 audio/video system	Yes
--------------------------------	-----



8461M

SINGLE-FAMILY KIT WITH QUADRA AND MINI, SIMPLEBUS SYSTEM



4793MC CORTEN FACEPLATE FOR QUADRA W/BUTTONS

Corten color faceplate for Quadra entrance panel with mechanical buttons.



4793MB BLACK FACEPLATE FOR QUADRA W/BUTTONS

Black faceplate for Quadra entrance panel with mechanical buttons



4793MA ALUMINIUM FACEPLATE FOR QUADRA W/BUTTONS

Aluminium colour faceplate for Quadra entrance panel with mechanical buttons




4791 ADAPTER PLATE FOR QUADRA

Plate allowing installation of the Quadra external unit in 1- and 2-module flush-mounted boxes by Comelit, Bticino and Urmet. Dimensions 137x236 mm



4792 RAIN SHIELD FOR QUADRA ENTRANCE PANEL

Rain shield in painted aluminum for Quadra entrance panel, grey colour. Dimensions (W x H x D): 99 x 210 x 41 mm.



1217 NAME TAG SHEETS FOR QUADRA ENTRANCE PANEL

The kit contains 10 sheets of adhesive labels for nameplates

**8461M****SINGLE-FAMILY KIT WITH QUADRA AND MINI, SIMPLEBUS SYSTEM****6711WS MINI HANDSET SMALL ADAPTER PLAQUE**

Mounting accessory for Mini Monitor when replacing Magis or Genius door entry monitors. White. Dimensions: 230x220x3mm.

**6719W Access. cables external passage for MINI HS. S2**

Wall support bracket for Mini monitor with handset allowing thru-routing of external cables.

**1405 DIGITAL EXCHANGE 2 QUADRA INPUTS. S2**

Audio/video switching module for audio/video kit systems. For use in systems with a maximum of 2 entrances with Quadra series external unit. Power supply from bus line. Dimensions: 35x90x58mm (2 DIN modules).

**6712 DESK BASE FOR MINI MONITOR**

Desk base converts the MINI monitor into a desktop version. Complete with 1 x 2 m labelled RJ45 cable for connecting the monitor terminals to the clasp or to a residential series jack. Dimensions: 145x190x120 mm. DESK BASE FOR MINI MONITOR

**6711W ADAPTER PLAQUE FOR MINI MONITOR W/ HANDSET. WHITE.**

Mounting accessory for Mini Monitor when replacing Magis or Genius door entry monitors. Complete with backplate art. 6710. White. Dimensions: 300x270x3 mm.



8461M

SINGLE-FAMILY KIT WITH QUADRA AND MINI, SIMPLEBUS SYSTEM



6710

BACKPLATE AND DISTRIBUTION TERMINAL FOR MINI MONITOR

Wall-mounting or residential series box backplate for MINI monitor, /BM versions with handset featuring magnetic induction for hearing aid wearers. Also includes riser distribution terminal Art. 1214/2C. Dimensions 145x100x4 mm.



1235A

NAMEPLATE LABEL PRINTING SOFTWARE

Dedicated software for the creation and printing of nameplate and information labels for Ikall, Vandalcom, Quadra and 316 Analog entrance panels. Requires use of adhesive labels art.1217, 1218, 1219 or art.1220. This software is available to download free of charge from the Comelit website



1409

MODULE FOR REMOTE CAMERAS. SIMPLEBUS 2

Remote camera module for Simplebus 2 2-wire digital systems. Allows management of up to 3 colour cameras in cyclical sequence from door entry monitors using a dedicated button. 12 Vac or 20 Vdc power supply. Dimensions: 60x85x35 mm (4 DIN modules).



1404

SIMPLEBUS2 DIGITAL SWITCHING DEVICE

Audio/video switching module for Simplebus 2 digital systems. To be used in systems with more than one entrance. Power supply from bus line. Dimensions: 60x85x35 mm (4 DIN modules).



1229A

ADDITIONAL RINGTONE ACCESSORY. S2

Wall-mounted accessory for additional ringtone for direct connection to 2-wire bus. Allows ringtone selection and adjustment of ringtone volume with privacy function, equipped with dip switches for user code programming, floor door call input terminals and call repeat. Fitted with distribution terminal art. 1214/2C. Dimensions: 125x95x24mm.

**8461M****SINGLE-FAMILY KIT WITH QUADRA AND MINI, SIMPLEBUS SYSTEM****6733W** **ADDITIONAL BUTTONS KIT FOR MINI MONITOR, WHITE**

Accessory for transforming MINI monitors Art 6700W-/BM and 6701W-/BM into versions with 8 buttons. Includes an 8-button faceplate and an electronic module for activating the buttons, which can be installed quickly without opening up the monitor.

**1256** **ACTUATOR RELAY. SIMPLEBUS 1 AND 2**

Intelligent Simplebus device for controlling a relay on board (12÷24 VAC/VDC - 10A max). For use and programming of the function required, follow the indications given in the technical documentation. It can be used in Simplebus system. Power supply: 12 VAC or 20 VDC. Dimensions: 66X85X35mm (4 DIN modules). Line branch terminal art. 1214/2C in equipment.