



**8461V**

**QUADRA + HANDSFREE MINI 1-FMLY KIT, SIMPLEBUS SYS.**



2-wire Simplebus door entry monitor kit comprised of: 1 Quadra series wall-mounted external unit art. 4893M, 1 power supply unit art. 1209, 1 Handsfree Mini series colour monitor art. 6721W, 1 distribution terminal art. 1214/2C and 1 line closure terminal art. 1216.

**AWARDS**





**8461V**

**QUADRA + HANDSFREE MINI 1-FMLY KIT, SIMPLEBUS SYS.**

**PRODUCTS IN THE KIT**



**4893M QUADRA ENTRANCE PANEL W/ BUTTONS. 2 WIRES**

Quadra series wall-mounted external video entry unit with mechanical buttons. Die-cast aluminium faceplate, wide-angle colour camera and a single LED for nighttime lighting. Indicator LED for call sent, lock-release activated, audio activated and system busy. Adjustment of speaker volume and audio balance. Power supply from bus line. External unit dimensions: 95x195x28 mm.

GENERAL DATA	
Type	Monoblock
Height (mm)	195
Width (mm)	95
Depth (mm)	28
Product weight (g)	300
Product color	Grey RAL 9006, Black RAL9005
Wall-mounted	Yes
COMPATIBLE SYSTEMS	
Simplebus 2 audio/video kit with power supply art. 1209	Yes
AUDIO FEATURES	
Microphone	6mm (Ø), Omnidirectional
Loudspeaker	36mm (Ø), 8 Ohm, 1W
CAMERA FEATURES	
Camera	Colours
Sensor type	1/4" CMOS
Lens optical dimensions (mm)	2.1
Angle of view (H x V - °)	85 x 72
Sensitivity (lux)	0.1 (colour)



**8461V**

**QUADRA + HANDSFREE MINI 1-FMLY KIT, SIMPLEBUS SYS.**

**ELECTRICAL CHARACTERISTICS**

Type of power supply	Power supply from video door entry bus
Supply voltage	33VDC
Maximum absorption (W)	8.25

**HARDWARE FEATURES**

Call type	Push-buttons
Type of buttons	Mechanical
Number of push-buttons (n°)	4
Backlight colour	White
Clamps	LL RTE COM DO SE- SE+C NC NO
Number of inputs (n°)	2
Number of outputs (n°)	2
Type of outputs	Relay (C-NO-NC, 10A@12÷24 VAC/VDC), SE: unlock pulse of 4A, holding current of 200mA for 12VAC / DC locks (maximum impedance 18 Ohm)

**SETTINGS**

Loudspeaker volume	Yes
Microphone volume	Yes

**ENVIRONMENTAL AND COMPLIANCE FEATURES**

IP protection rating	IP54
Vandal Resistant rating (IK code)	IK08
Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	IV
CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

**MAIN FUNCTIONS**

Door opener	Yes
-------------	-----



**8461V**

**QUADRA + HANDSFREE MINI 1-FMLY KIT, SIMPLEBUS SYS.**

**MAIN FUNCTIONS**

Number of auxiliary relays (n°)	1
Input for local door release button	Yes
Door open signaling input	Yes

**GENERAL FEATURES**

Type of finishing materials	Polycarbonate, Aluminium alloy
Acoustic signalling	Yes
Visual signalling	Yes
Speech synthesis	Yes



**8461V**

**QUADRA + HANDSFREE MINI 1-FMLY KIT, SIMPLEBUS SYS.**



**6721W SIMPLEBUS2 MINI HANDSFREE DOOR ENTRY MONITOR**

Wall-mounted hands-free monitor with full-duplex audio and 4.3" / 16:9 colour screen. Allows brightness control, plus adjustment of the ringtone volume, which can be customised by choosing one of several different melodies. Equipped as standard with 5 sensitive touch backlit controls for audio activation, door-opening, self-ignition, switchboard call, privacy service and LED signalling for the door status. Manages floor door calls as standard. Option of adding 3 additional buttons with accessory Art. 6734W. Complete with 2 x 8-position DIP-SWITCH for user code programming and button programming. The wall-mounting or residential series box backplate and riser distribution terminal Art. 1214/2C are included. The monitor can only be used in 2-wire Simplebus2 systems. Dimensions: 115x160x22mm.

GENERAL DATA	
Height (mm)	160
Width (mm)	115
Depth (mm)	22
Product color	White RAL9003
Type of finishing materials	ABS
Product weight (g)	500
Wall-mounted	Yes
Desk base-mounted	Yes, with a dedicated accessory
COMPATIBLE SYSTEMS	
Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes
DISPLAY	
Display size (")	4.3



**8461V**

**QUADRA + HANDSFREE MINI 1-FMLY KIT, SIMPLEBUS SYS.**

**DISPLAY**

Aspect Ratio	16:9
Resolution (pixels)	480x272

**AUDIO FEATURES**

Microphone	6mm (Ø), Omnidirectional
Loudspeaker	36mm (Ø), 40 Ohm, 1W
Technologies implemented	Full-Duplex

**ELECTRICAL CHARACTERISTICS**

Type of power supply	Power supply from video door entry bus
Supply voltage	22÷34 VDC (Bus)
Absorption in stand-by (W)	0.05
Maximum absorption (W)	8.8

**HARDWARE FEATURES**

Type of buttons	Capacitive
Service buttons	Lock-release, Answer, Silent (Privacy), Door open
No. of programmable buttons for additional functions	2 (5 with accessory art. 6734W)
Clamps	L L CFP1 CFP2
Removable terminals	Yes

**SETTINGS**

Loudspeaker volume	Yes
Microphone volume	Yes
Ringtone volume	Yes
Screen brightness control	Yes
Screen contrast	Yes
Screen colour	Yes

**ENVIRONMENTAL AND COMPLIANCE FEATURES**



**8461V**

**QUADRA + HANDSFREE MINI 1-FMLY KIT, SIMPLEBUS SYS.**

IP protection rating	IP30
Operating temperature (°C)	5 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 75
Environmental class	I
CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

**GENERAL FEATURES**

Door opening on call (Doctor)	Yes
Door opener	Yes
Self Activation	Yes
CPS call	Yes
Intercom calls	Yes
Actuator control	Yes
Multiple address	Yes
Outside door call input	Yes
Sending alarm calls	Yes
Silent mode (Privacy)	Yes
Automatic answer (handsfree)	Yes
Door open signaling	Yes
Customisable ringtone	Yes



**8461V**

**QUADRA + HANDSFREE MINI 1-FMLY KIT, SIMPLEBUS SYS.**



**1209 SIMPLEBUS2 VIDEO KIT POWER SUPPLY UNIT**

33 VDC power supply unit with overload and short circuit protection devices. It has two separate continuous outputs: one to power the external unit and electric lock, and the other to power the monitor. Input voltage 110-240 VAC. Dimensions: 106x62x89mm (6 DIN modules).

MAIN FEATURES	
Supply voltage	110÷240
Max. current delivered (A)	1.2
Applicable to DIN rail	Yes
Number of DIN modules (n°)	6
GENERAL DATA	
Height (mm)	62
Width (mm)	106
Depth (mm)	89
Type of finishing materials	Plastic
Product color	White
Operating temperature (°C)	-5 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 95
COMPATIBILITY	
Kit audio/video system	Yes
ELECTRICAL SPECIFICATIONS	
Maximum power delivered (W)	37





**8461V**

**QUADRA + HANDSFREE MINI 1-FMLY KIT, SIMPLEBUS SYS.**



**1216 SIMPLEBUS2 LINE TERMINATION TERMINAL**

Line termination terminal. To be mounted at the end of the riser, according to the indications given in the technical documentation, to optimise distribution of the signals.

GENERAL FEATURES	
Input connector	Terminal block
CE certifications	EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)
MAIN FEATURES	
Operating temperature (°C)	-5 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 95
COMPATIBILITY	
Simplebus 2 audio/video system	Yes

**8461V****QUADRA + HANDSFREE MINI 1-FMLY KIT, SIMPLEBUS SYS.****ACCESSORIES****4793MC CORTEN FACEPLATE FOR QUADRA W/BUTTONS**

Corten color faceplate for Quadra entrance panel with mechanical buttons.

**4793MB BLACK FACEPLATE FOR QUADRA W/BUTTONS**

Black faceplate for Quadra entrance panel with mechanical buttons

**4793MA ALUMINIUM FACEPLATE FOR QUADRA W/BUTTONS**

Aluminium colour faceplate for Quadra entrance panel with mechanical buttons

**4791 ADAPTER PLATE FOR QUADRA**

Plate allowing installation of the Quadra external unit in 1- and 2-module flush-mounted boxes by Comelit, Bticino and Urmet. Dimensions 137x236 mm

**4792 RAIN SHIELD FOR QUADRA ENTRANCE PANEL**

Rain shield in painted aluminum for Quadra entrance panel, grey colour. Dimensions (W x H x D): 99 x 210 x 41 mm.

**1217 NAME TAG SHEETS FOR QUADRA ENTRANCE PANEL**

The kit contains 10 sheets of adhesive labels for nameplates



**8461V**

**QUADRA + HANDSFREE MINI 1-FMLY KIT, SIMPLEBUS SYS.**

**ACCESSORIES**



**6732 DESK BASE FOR HANDSFREE MINI MONITOR**

Desk base for desktop conversion of Handsfree Mini monitor. Complete with 1x 2 metre cable with RJ45 connector to connect monitor terminals to the coupler or domestic series socket. Dimensions: 140x190x140mm.



**6720 Access. cables external passage for MINI HF. S2**

Wall support bracket for handsfree Mini monitor allowing thru-routing of external cables.



**1405 DIGITAL EXCHANGE 2 QUADRA INPUTS. S2**

Audio/video switching module for audio/video kit systems. For use in systems with a maximum of 2 entrances with Quadra series external unit. Power supply from bus line. Dimensions: 35x90x58mm (2 DIN modules).



**6710 BACKPLATE AND DISTRIBUTION TERMINAL FOR MINI MONITOR**

Wall-mounting or residential series box backplate for MINI monitor, /BM versions with handset featuring magnetic induction for hearing aid wearers. Also includes riser distribution terminal Art. 1214/2C. Dimensions 145x100x4 mm.



**1235A NAMEPLATE LABEL PRINTING SOFTWARE**

Dedicated software for the creation and printing of nameplate and information labels for Ikall, Vandalcom, Quadra and 316 Analog entrance panels. Requires use of adhesive labels art.1217, 1218, 1219 or art.1220. This software is available to download free of charge from the Comelit website



**8461V**

**QUADRA + HANDSFREE MINI 1-FMLY KIT, SIMPLEBUS SYS.**

**ACCESSORIES**



**1409**

**MODULE FOR REMOTE CAMERAS. SIMPLEBUS 2**

Remote camera module for Simplebus 2 2-wire digital systems. Allows management of up to 3 colour cameras in cyclical sequence from door entry monitors using a dedicated button. 12 Vac or 20 Vdc power supply. Dimensions: 60x85x35 mm (4 DIN modules).



**1404**

**SIMPLEBUS2 DIGITAL SWITCHING DEVICE**


Audio/video switching module for Simplebus 2 digital systems. To be used in systems with more than one entrance. Power supply from bus line. Dimensions: 60x85x35 mm (4 DIN modules).



**1229A**

**ADDITIONAL RINGTONE ACCESSORY. S2**

Wall-mounted accessory for additional ringtone for direct connection to 2-wire bus. Allows ringtone selection and adjustment of ringtone volume with privacy function, equipped with dip switches for user code programming, floor door call input terminals and call repeat. Fitted with distribution terminal art. 1214/2C. Dimensions: 125x95x24mm.



**6733W**

**ADDITIONAL BUTTONS KIT FOR MINI MONITOR, WHITE**

Accessory for transforming MINI monitors Art 6700W-/BM and 6701W-/BM into versions with 8 buttons. Includes an 8-button faceplate and an electronic module for activating the buttons, which can be installed quickly without opening up the monitor.

**8461V****QUADRA + HANDSFREE MINI 1-FMLY KIT, SIMPLEBUS SYS.****ACCESSORIES****1256****ACTUATOR RELAY. SIMPLEBUS 1 AND 2**

Intelligent Simplebus device for controlling a relay on board (12÷24 VAC/VDC - 10A max). For use and programming of the function required, follow the indications given in the technical documentation. It can be used in Simplebus system. Power supply: 12 VAC or 20 VDC. Dimensions: 66X85X35mm (4 DIN modules). Line branch terminal art. 1214/2C in equipment.